

Side channel analysis of some hash based MACs:A response to SHA-3 requirements

Gauravaram, Praveen; Okeya, Katsuyuki

Publication date:
2008

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Gauravaram, P. (Author), & Okeya, K. (Author), (2008). Side channel analysis of some hash based MACs:A response to SHA-3 requirements. Sound/Visual production (digital) <http://www2.mat.dtu.dk/sha3/>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Side channel analysis of some hash based MACs:
A response to SHA-3 requirements

ICICS 2008

Praveen Gauravaram¹ and Katsuyuki Okeya²

Department of Mathematics ¹
Technical University of Denmark (DTU)
Denmark.

Systems Development Laboratory²
Hitachi, Ltd
Japan.

Overview of the Presentation

- Research problem
- Hash functions and hash based MACs
- SCA attacks and our model to analyse hash based MACs
- DPA of recently proposed hash based MACs
- Summary and open questions

Research Problem.

Motivation

■ Background

- Cryptanalysis of standard hash functions (MD5 & SHA-1)
- Generic attacks on the Merkle-Damgård structure
- Necessity for new hashing methods
- AHS competition of NIST to augment FIPS 180-2 secure hash standard (SHS)
- The new SHS will be SHA-3 family.

■ Requirement of a hash submission to the AHS competition

- Support for the FIPS applications (FIPS 198 HMAC)
- Consideration of side channel attacks (SCA) on the hash based MACs
 1. Resistance to SCA for HMAC configuration
 2. Resistance to SCA for other MAC configurations

Research Problem

■ Hypothesis

- New hash and compression function modes as SHA-3 candidates
- Compression function modes could be based on block ciphers (PGV)

■ SHA-3 requirement

- Hash modes should define either a HMAC or a dedicated MAC mode
- Any MAC mode should have protection from the SCA attacks

■ Research questions

- Security of recent hash and compression function modes in the HMAC setting against SCA?
- Security of recently proposed alternatives to HMAC against SCA?
- How such an analysis can contribute to the AHS competition?


Our approach

- Classify to be analysed MACs into two categories
 - *Type-1: Provably secure MAC alternatives to NMAC/HMAC*
Examples: BNMAC, KMDP, EMD MAC, Multi-lane NMAC and O-NMAC
 - *Type-2: HMAC/NMAC configuration of the compression and hash modes*
Examples: MDC2, Grindahl, MAME and Wide-pipe hash
- MAC schemes with no hash analysis
Examples: BNMAC, O-NMAC
- DPA attack model assumes that the block cipher is DPA resistant

Hash functions and hash based MACs


Hash Functions

- $H : \{0, 1\}^* \rightarrow \{0, 1\}^n, H(M) = Y$
- Merkle-Damgård iterative structure
- Popular hashes: MD4, MD5, SHA-0/1, SHA-224/256 and SHA-384/512



MAC Algorithms

- Verify the integrity and authenticity of the information
- Secure MAC: Hard to find a new $(m, \text{MAC}(m))$ pair even after seeing a few of them
- Attacks include forgery and key-recovery
- Forgeries
 - Universal
 - Selective
 - Existential
- HMAC is FIPS PUB 198 standard




- NMAC is a variant of HMAC.


SCA attacks and our model

Side Channel Attacks

- Serious threat to the computing devices that often use secret-key algorithms
- Side channel information is linked with the secret key
- Correlate physical measurements and computing time with the internal state correlated to the secret key
- Reveal secret internal state or the key itself




DPA attack model



■ DPA attack:

1. Guess some bit of y
2. Classify x into two groups.
 - (a) Group 1: target bit of $z = 1$
 - (b) Group 0: target bit of $z = 0$
3. Measure the output power signal for each group
4. Compute average power signal for each group and measure their difference
5. Use DPA bias signal to verify the guess of y
6. Repeat (1)-(5) to recover y

Reverse DPA attack model




■ RDPA attack:

1. Guess some bit of y
2. Measure the power signal
3. Retrieve and classify z into two groups
 - (a) Group 1: target bit of $x = 1$
 - (b) Group 0: target bit of $x = 0$
4. Compute average power signal for each group and measure their difference
5. Use DPA bias signal to verify the guess of y
6. Repeat (1)-(5) to recover y


DPA analysis of recently proposed hash based MACs

DPA attack on BNMAC




- Mount DPA attack on $H_i \oplus m_{2i+1}$ (or $k_2 \oplus m_1$) and recover k_2
- Padding procedure in BNMAC does not depend on the message length
- Recovery of k_1 depends on the architecture of f
- k_2 is enough to forge BNMAC:
 1. Ask BNMAC tag for $m = m_1 \| m_2 \| \dots \| m_{2L-1} \| m_{2L}$
 2. Set $m_3^* = H_1 \oplus (m_1 \oplus k_2)$ and $m_4^* = m_2$
 3. Set $m^* = m_1 \| m_2 \| m_3^* \| m_4^* \dots \| m_{2L-1} \| m_{2L}$
 4. $\text{BNMAC}_{k_1, k_2}(m) = \text{BNMAC}_{k_1, k_2}(m^*)$

KMDP using PGV schemes




■ Security against DPA attacks is almost similar to that of NMAC/HMAC

■ RDPA attack on KMDP based on Davies-Meyer:




1. Mount RDPA on $P(H_1) \oplus E_{m_2}(P(H_1)) = H_2$ using N^2 of $m_1 || m_2$ and recover N values of $P(H_1)$ and then H_1
2. Mount RDPA on $k \oplus E_{m_1}(k) = H_1$ using N of H_1 to recover k

Grindahl and MDC2 compression functions



- No target XOR operation when P is ideal
- SCA resistant when P is ideal
- MDC2 which uses Matyas-Meyer-Oseas also does not expose any target XOR operation



Summary of results

MAC function	Matyas-Meyer-Oseas	Miyaguchi-Preneel	Davies-Meyer
BNMAC	PK(EF)	CK(UF)	CK(UF)
EMD	N/A	N/A	PK(NG)
KMDP	NO	NO	CK(UF)
Multi-lane NMAC	N/A	N/A	PK(NG)
O-NMAC	NO	NO	NO
NMAC	NO	NO	PK(NG)

- Wide-pipe hash in the HMAC mode has the same DPA security as HMAC
- MAME compression function in the HMAC mode is DPA resistant

Open questions

Open questions

- How to design a block cipher based multi-property preserving hash construction which is also a SCA resistant when it is instantiated with any of the secure PGV schemes
- Design of a provably secure MAC construction using HAIFA and double-pipe hash invoked with secure PGV schemes and their analysis w.r.t SCA attacks
- What type of alternatives to MD can be plugged into NMAC/HMAC?

Acknowledgments

- Support from the Danish Research Council for Technology and Innovation for the project SHA-3 hash function (<http://www2.mat.dtu.dk/sha3/>)
- Nasour Bagheri (DTU, Denmark)
- Julia Borghoff (DTU, Denmark)
- Bill Burr (NIST, USA)
- Shoichi Hirose (University of Fukui, Japan)
- John Kelsey (NIST, USA)
- Lars Knudsen (DTU, Denmark)
- Gregor Leander (DTU, Denmark)
- Krystian Matusiewicz (DTU, Denmark)
- Søren Thomsen (DTU, Denmark)
- Erik Zenner (DTU, Denmark)